Company			Contact			
Dept.			Phone			
Street			Fax			
PC / City			E-Mail			
Country			www.			
Project					Delivery ca.	CW
Use / Application						essing, Hospitals, oratories, Changing Rooms, g
Particularities			e.g. Air Treatn Cheese Ripen		Persons in t	he Room O yes O no
Environment	Length Width	Height	= m³		ir- emperature	Relative Humidity (RH), min./max. %
Cubic Measures	x ;				°C	/
Options	Obstacles in the Ro Monitoring System	•	O no (see en		,	no (where? see remarks)
	Worldring Oyston	O yes O no	_	-	•	(-35% mW) Direct Emitters
Units	Recircu Type	irculation	Direct Emitters culation Reference: per 50-60 m³ = 1 unit (2036)			
	LSK2030-2K A	up to	180 m³/h	D 203	36, 2030, 2020	Direct irradiation, motion detector compulsory
				DE 203	3 86, 2030, 2020	Suspended from ceiling, with protection screen
	UVR2250-2	up to	220 m³/h	WI 203	3 6, 2030, 2020	Wall mounted, with protection screen
	UVR2250-2	up to	450 m³/h	WI 203	R 6, 2030, 2020	Wall mounted, (fitted not lower than 2.1m), with sight protection
				SV 203		Over doors
			<u> </u>			
Accessories / R	emarks					
Accessories / R	emarks					
Accessories / R	emarks					
Accessories / R	emarks					

Name/Company

Date